



Thijs Talenstraat 1
NL-7913 ZX Hollandscheveld
Tel.: + 31 (0)528 34 28 92
Fax.: + 31 (0)528 34 28 93
site: www.pneumatic.nl
e-mail: info@pneumatic.nl

Postbus 14
NL-7913 ZG Hollandscheveld
VAT/BTW nr.: NL8158.43.859.B01
Bankrek.nr.: 31.66.09.072
IBAN nr.: NL89 RABO 0316609072
Swift: RABONL 2U

VV-100 stands for a low cost, high performance vacuum venturi, that's produced by ICH. The venturi gives a high vacuum level, till 90% (at +/- 6bar).

The venturi is made from anodised aluminium the internal parts are from brass. The venturi has no moving parts, this makes it very reliable and also gives it a high durability

This venturi can be used for: pick and place applications, the evacuation of moulds, the finding of leakages and so on.

Article code:	VV-100-12H
Vacuum level:	80~90%
Vacuum flow:	45 NL/min
Air consumption:	60 NL/min
Vacuum port:	G1/2(female)
Pressure port:	G1/4(female)
Exhaust port:	G1/4(female)
Dimensions:	50*40*28 (mm)
Material body:	Aluminium
Material jetpipe & nozzle:	Brass

